

DRILL COLLARS

OD	ID	Connection	Bevel Diameter	Length	Make-up Torque	Torsional Strength	BSR	Weight (Slick)	Weight (Spiral)	Elevator Recess		Slip Recess			
(in)	(in)	(in)	(in)	(ft)	(ft.lbs)	(ft.lbs)		(lbs)	(lbs)	Depth	Radius	OD	Depth	Angle	
										(in)		(in)	(in)	(°)	
4 3/4	2 1/4	NC38	4 37/64	31	9,990	17,600	1.92	1,430	1,360	4 1/4	1/4	1/8	4 3/8	3/16	3.5
6 1/4	2 13/16	NC46	5 29/32	31	22,400	39,500	2.64	2,550	2,420	5 5/8	5/16	1/8	5 3/4	1/4	5
6 1/4	2 13/16	NC50	5 59/64	31	23,000	40,500	1.71	2,550	2,420	5 5/8	5/16	1/8	5 3/4	1/4	5
6 1/2	2 13/16	NC46	6 3/32	31	22,400	39,500	3.07	2,810	2,660	5 7/8	5/16	1/8	6	1/4	5
6 1/2	2 13/16	NC50	6 7/64	31	29,700	52,200	2.03	2,810	2,660	5 7/8	5/16	1/8	6	1/4	5
6 3/4	2 13/16	NC46		31	23,220			3,080	2,920	6	3/8	3/16	6 1/4	1/4	5
6 3/4	2 13/16	NC50	6 19/64	31	32,300	56,800	2.37	3,080	2,920	6	3/8	3/16	6 1/4	1/4	5
8	2 13/16	6 5/8 Reg	7 33/64	31	53,300	85,400	2.6	4,580	4,330	7 1/4	3/8	3/16	7 1/2	1/4	5
8 1/4	2 13/16	6 5/8 Reg	7 45/64	31	53,300	85,400	2.93	4,910	4,630	7 1/2	3/8	3/16	7 3/4	1/4	5



A Division of
Texas Steel Conversion, Inc.

281-452-2260

7203 Miller Road #2 • Houston, Texas 77049 • sales@tsc-hdd.com

tsc-hdd.com